

OVERVIEW



| | |
|--|------------------|
| 1. Headphone / microphone combo jack (3.5mm) | 3. Thunderbolt 4 |
| 2. Thunderbolt 4 | 4. Power button |

Notes:

- Optional nano-SIM card slot on the rear side (not shown on the sample product above)

PERFORMANCE

Processor

Processor Family

11th Generation Intel® Core™ i5 / i7 Processor

Processor**

| Processor Name | Cores | Threads | Base Frequency | Max Frequency | Cache | Memory Support | Processor Graphics |
|----------------|-------|---------|----------------|---------------|-------|----------------|-------------------------|
| Core i5-1130G7 | 4 | 8 | 1.8GHz | 4.0GHz | 8MB | LPDDR4x-4266 | Intel Iris® Xe Graphics |
| Core i5-1140G7 | 4 | 8 | 1.8GHz | 4.2GHz | 8MB | LPDDR4x-4266 | Intel Iris Xe Graphics |
| Core i7-1160G7 | 4 | 8 | 2.1GHz | 4.4GHz | 12MB | LPDDR4x-4266 | Intel Iris Xe Graphics |
| Core i7-1180G7 | 4 | 8 | 2.2GHz | 4.6GHz | 12MB | LPDDR4x-4266 | Intel Iris Xe Graphics |

Operating System

Operating System**

- Windows® 10 Pro 64
- Windows 10 Home 64
- Windows 10 IoT Enterprise LTSC
- Windows 11 Pro 64
- Windows 11 Home 64
- Windows 11 DG Windows 10 Pro 64
- Linux
- Ubuntu Linux
- No operating system

Graphics

Graphics

| Graphics | Type | Memory | Key Features |
|------------------------|------------|--------|--------------|
| Intel Iris Xe Graphics | Integrated | Shared | DirectX® 12 |

Monitor Support

Monitor Support

Supports up to 3 independent displays via native display and 2 external monitors; supports external monitors via Thunderbolt™ (5120x3200@60Hz)

Chipset

Chipset

Intel SoC (System on Chip) platform

Memory

Max Memory^[2]

- 8GB soldered memory, not upgradable
- 16GB soldered memory, not upgradable

Memory Slots

Memory soldered to systemboard, no slots, dual-channel

Memory Type

LPDDR4x-4266

Notes:

1. The max memory is based on the test results with current Lenovo® memory offerings. The system may support more memory as the technology develops.
2. 8GB memory is NOT available in EMEA

Storage

Storage Support

ThinkPad X1 Nano Gen 1

One drive, up to 1TB M.2 2242 SSD

Storage Type

| Disk Type | Interface | RPM | Security |
|--------------|------------------------|-----|----------|
| M.2 2242 SSD | PCIe NVMe, PCIe 3.0 x4 | - | - |

Removable Storage

Optical

None

Card Reader

No card reader

Multi-Media

Audio Chip

High Definition (HD) Audio, Realtek® ALC3306 codec

Speakers

Stereo speakers, 2W x2 woofers and 1W x2 tweeters, Dolby® Atmos®

Microphone

Four array microphones, 360° far-field

Camera

IR & 720p hybrid, with privacy shutter, fixed focus

Battery

Battery

Integrated Li-Polymer 48Wh battery, supports Rapid Charge (charge up to 80% in 1hr)

Max Battery Life^[1]

MobileMark® 2018: 13.6 hr

JEITA 2.0: 22.87 hr

Notes:

- All battery life claims are approximate maximum and based on results using the MobileMark 2014, MobileMark 2018, JEITA 2.0, continuous 1080p video playback (with 150nits brightness and default volume level) or Google Power Load Test (PLT) battery-life benchmark tests. Actual battery life will vary and depends on many factors such as product configuration and usage, software use, wireless functionality, power management settings, and screen brightness. The maximum capacity of the battery will decrease with time and use.

Power Adapter

Power Adapter^{**[1]}

- 65W USB-C slim (3-pin) AC adapter
- 65W USB-C slim (2-pin) AC adapter
- No power adapter

Notes:

- No power adapter is for special bid only

DESIGN

Display

Display^{**[1]}

| Size | Resolution | Touch | Type | Brightness | Surface | Aspect Ratio | Contrast Ratio | Color Gamut | Viewing Angle | Key Features |
|-------|----------------|-------------|------|------------|------------------------------|--------------|----------------|-------------|---------------|--------------|
| 13.0" | 2K (2160x1350) | None | IPS | 450 nits | Anti-glare | 16:10 | 1000:1 | 100% sRGB | 170° | Low power |
| 13.0" | 2K (2160x1350) | Multi-touch | IPS | 450 nits | Anti-reflection, Anti-smudge | 16:10 | 1000:1 | 100% sRGB | 170° | Low power |

Touchscreen

- Capacitive-type on-cell multi-touch, supports 10-point touch
- Non-touch

Notes:

1. California Electronic Waste Recycling Fee
In California, per state law, Lenovo charges an electronic waste recycling fee on this covered device at the time of sale of the product.
For more information, go to <https://www.calrecycle.ca.gov/Electronics/Consumer>

Input Device**Keyboard**

6-row, spill-resistant, multimedia Fn keys with Unified Communications controls

Keyboard Backlight

LED backlight

UltraNav™

TrackPoint® pointing device and glass surface multi-touch touchpad

Mechanical**Dimensions (WxDxH)**

| Models | Dimensions |
|------------------|---|
| Touch models | 292.9 x 207.8 x 14.27-17.2 mm (11.53 x 8.18 x 0.56-0.68 inches) |
| Non-touch models | 292.8x 207.7 x 13.87-16.7 mm (11.53 x 8.18 x 0.55-0.66 inches) |

Weight^[1]

| Models | Weight |
|------------------------------|-------------------|
| Non-touch with Wi-Fi® models | 907 g (1.99 lbs) |
| Non-touch with WWAN models | 939 g (2.07lbs) |
| Touch with Wi-Fi models | 969 g (2.14 lbs) |
| Touch with WWAN models | 1001 g (2.21 lbs) |

Case Color**

- Black, paint
- Black, weave

Case Material

Carbon fiber (top), magnesium alloy (bottom)

Notes:

1. The system weight varies depending on configurations

CONNECTIVITY**Network****Onboard Ethernet**

Ethernet support via optional Lenovo USB-C to Ethernet Adapter

WLAN + Bluetooth^[1]

Intel Wi-Fi 6 AX201, 802.11ax 2x2 Wi-Fi + Bluetooth 5.2

WWAN[2]**

- Wireless WAN upgradable to 4G or 5G
- Integrated Mobile Broadband 4G LTE-A, CAT9, Fibocom L850-GL, M.2 card
- Qualcomm® Snapdragon™ X55 5G Modem M.2 card - RF System with embedded eSIM functionality
- No support

SIM Card

- Gemalto eSIM
- No SIM card inbox

NFC

No support

Notes:

1. Intel WiFi 6 full features might be limited by country level restrictions
Bluetooth 5.2 is supported with driver version 22.30 and later
2. For non-WWAN model, it means the model is NOT WWAN upgradable

Ports^[1]

Standard Ports

- 2x Thunderbolt 4 / USB4™ 40Gbps (support data transfer, Power Delivery 3.0 and DisplayPort™ 1.4a)
- 1x Headphone / microphone combo jack (3.5mm)

Optional Ports

1x Nano-SIM card slot (WWAN model)

Notes:

1. The transfer speed of following ports will vary and, depending on many factors, such as the processing speed of the host device, file attributes and other factors related to system configuration and your operating environment, will be slower than theoretical speed.
USB 2.0: 480 Mbit/s;
USB 3.2 Gen 1 (SuperSpeed USB 5Gbps, formerly USB 3.0 / USB 3.1 Gen 1): 5 Gbit/s;
USB 3.2 Gen 2 (SuperSpeed USB 10Gbps, formerly USB 3.1 Gen 2): 10 Gbit/s;
USB 3.2 Gen 2x2 (SuperSpeed USB 20Gbps): 20 Gbit/s;
Thunderbolt 3: 40 Gbit/s;
FireWire 400: 400 Mbit/s;
FireWire 800: 800 Mbit/s

Monitor Cable

Monitor Cable

- Lenovo USB-C to VGA Adapter
- No monitor cable

SECURITY & PRIVACY

Security

Security Chip**

- Discrete TPM 2.0, TCG certified
- Firmware TPM 2.0 integrated in chipset
- Disabled (in some regions)

Smart Card Reader

No smart card reader

Fingerprint Reader

Touch style fingerprint reader on palm rest, match-on-chip

BIOS Security

- Supervisor password
- Power-on password
- Hard disk password
- Firmware Resiliency 2.0

Other Security

- ThinkShutter camera cover
- (Optional) IR camera for Windows Hello
- (Optional) Human Presence Detection

MANAGEABILITY

System Management

System Management

- Intel vPro Technology, DASH

- None

SERVICE

Warranty

Base Warranty**

- 1-year depot service
- 1-year depot with 2-year system board service
- 1-year limited onsite service
- 1-year + 2-year depot service
- 1-year + 2-year limited onsite service
- 3-year (1-yr battery) depot service
- 3-year (1-yr battery) limited onsite service
- No base warranty

ENVIRONMENTAL

Operating Environment

Temperature^[1]

- Operating: 5°C (41°F) to 35°C (95°F)
- Storage and transportation in original shipping package: -20°C (-4°F) to 60°C (140°F)
- Storage without package: 5°C (41°F) to 43°C (109°F)

Humidity

- Operating: 8% to 95% at wet-bulb temperature 23°C (73°F)
- Storage and transportation: 5% to 95% at wet-bulb temperature 27°C (81°F)

Altitude

Maximum altitude (without pressurization): 3048 m (10,000 ft)

Notes:

1. When you charge the battery, its temperature must be no lower than 10°C (50°F)

ACCESSORIES

Bundled Accessories

Bundled Accessories***

- Lenovo USB-C to Ethernet Adapter
- Lenovo USB-C Port Replicator
- None

CERTIFICATIONS

Green Certifications

Green Certifications

- EPEAT™ Gold
- ENERGY STAR® 8.0
- TCO
- RoHS compliant

Other Certifications

Mil-Spec Test

MIL-STD-810H military test passed

Other Certifications

(Optional) Intel Evo™ Platform

- Feature with ** means that only one offering listed under the feature is configured on selected models.
- Feature with *** means that one or more offerings listed under the feature could be configured on selected models.
- Lenovo reserves the right to change specifications or other product information without notice. Lenovo is not responsible for photographic or typographical errors. LENOVO PROVIDES THIS PUBLICATION “AS IS,” WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some jurisdictions do not allow disclaimer of express or implied warranties in certain transactions, therefore this disclaimer may not apply to you.
- The specifications on this page may not be available in all regions, and may be changed or updated without notice.

