

OVERVIEW





| 1. Pen slot * | 6. Thunderbolt 4 |
|--|------------------------------|
| 2. Headphone / microphone combo jack (3.5mm) | 7. Thunderbolt 4 |
| 3. Nano-SIM card slot * | 8. HDMI 2.0 |
| 4. USB 3.2 Gen 1 | 9. USB 3.2 Gen 1 (Always On) |
| 5. Kensington Nano Security Slot | 10. Smart card reader * |

Notas

• Items with * are only available on selected models



PERFORMANCE

Processor

Processor Family

11th Generation Intel® Core™ i5 / i7 Processor

Processor**

| Processor Name | Cores | Threads | Base Frequency | Max Frequency | Cache | Memory Support | Processor Graphics |
|----------------|-------|---------|----------------|---------------|-------|----------------|-------------------------|
| Core i5-1135G7 | 4 | 8 | 2.4GHz | 4.2GHz | 8MB | LPDDR4x-4266 | Intel Iris® Xe Graphics |
| Core i5-1145G7 | 4 | 8 | 2.6GHz | 4.4GHz | 8MB | LPDDR4x-4266 | Intel Iris Xe Graphics |
| Core i7-1165G7 | 4 | 8 | 2.8GHz | 4.7GHz | 12MB | LPDDR4x-4266 | Intel Iris Xe Graphics |
| Core i7-1185G7 | 4 | 8 | 3.0GHz | 4.8GHz | 12MB | LPDDR4x-4266 | Intel Iris Xe Graphics |

Operating System

Operating System**[1]

- Windows® 11 Pro
- Windows 11 Home
- Windows 11 Home Single Language
- Windows 11 DG Windows 10 Pro 64
- Windows 10 Pro 64
- Windows 10 Home 64
- Windows 10 Home 64 Single Language
- Linux
- Ubuntu Linux
- No operating system

Notes:

1. Some features may not be supported on the system with Linux preload, including but not limited to Intel RST RAID, MIPI computer vision camera, WWAN, Human Presence Detection, etc.

Graphics

Graphics

| Graphics | Туре | Memory | Key Features | |
|------------------------|------------|--------|---------------|--|
| Intel Iris Xe Graphics | Integrated | Shared | DirectX® 12.1 | |

Monitor Support

Monitor Support[1]

Supports up to 4 independent displays (native display and 3 external monitors via Thunderbolt™ and HDMI®)

- Thunderbolt supports up to 5K@60Hz
- HDMI supports up to 4K@60Hz

Notes:

1. Refresh rates >60hz also supported, however max resolution will be limited.

Chipset

Chipset

Intel SoC (System on Chip) platform

Memory

Max Memory[1]

- 8GB soldered memory, not upgradable
- 16GB soldered memory, not upgradable
- 32GB soldered memory, not upgradable

Memory Slots

Memory soldered to systemboard, no slots, dual-channel

Memory Type

ThinkPad X13 Yoga Gen 2 (Intel)



LPDDR4x-4266

Notes:

1. The max memory is based on the test results with current Lenovo® memory offerings. The system may support more memory as the technology develops.

Storage

Storage Support[1]

One drive, up to 2TB M.2 2280 SSD

Storage Type**

| Disk Type | Interface | Security |
|--------------|------------------------------------|----------|
| M.2 2280 SSD | PCIe® NVMe®, PCIe x4 | Opal 2.0 |
| M.2 2280 SSD | PCIe NVMe, PCIe 4.0 x4 Performance | Opal 2.0 |

Notes:

1. The storage capacity supported is based on the test results with current Lenovo storage offerings. The system may support larger storage as the technology develops.

Removable Storage

Card Reader

No card reader

Multi-Media

Audio Chip

High Definition (HD) Audio, Realtek® ALC3286 codec

Speakers

Stereo speakers, 2W x2, Dolby® Audio™

Microphone

Dual-microphone array, far-field

Camera**

- HD 720p, with privacy shutter, fixed focus
- HD 720p + IR hybrid, with privacy shutter, fixed focus

Sensor

Sensors

- · Accelerometer (G) sensor
- Gyroscope sensor
- Proximity (P) sensor (WWAN models)

Battery

Battery

Integrated Li-Polymer 52.8Wh battery, supports Rapid Charge (charge up to 80% in 1hr) with 65W AC adapter

Max Battery Life[1]

MobileMark® 2018: 12.2 hr JEITA 2.0: 18.9 hr

Notes:

1. All battery life claims are approximate maximum and based on results using the MobileMark 2014, MobileMark 2018, JEITA 2.0, continuous 1080p video playback (with 150nits brightness and default volume level) or Google Power Load Test (PLT) battery-life benchmark tests. Actual battery life will vary and depends on many factors such as product configuration and usage, software use, wireless functionality, power management settings, and screen brightness. The maximum capacity of the battery will decrease with time and use.

Power Adapter

Power Adapter**[1]

- 45W USB-C® (2-pin) AC adapter, supports PD 3.0, 100-240V, 50-60Hz
- 45W USB-C (3-pin) AC adapter, supports PD 3.0, 100-240V, 50-60Hz

ThinkPad X13 Yoga Gen 2 (Intel)



- 65W USB-C (2-pin) AC adapter, supports PD 3.0, 100-240V, 50-60Hz
- 65W USB-C (3-pin) AC adapter, supports PD 3.0, 100-240V, 50-60Hz
- 65W USB-C slim (2-pin) AC adapter, supports PD 3.0, 100-240V, 50-60Hz
- 65W USB-C slim (3-pin) AC adapter, supports PD 3.0, 100-240V, 50-60Hz

Notes:

1. AC adapter offerings depend on the country.

DESIGN

Display

Display**[1]

| Size | Resolution | Touch | Туре | Brightness | Surface | Aspect Ratio | Contrast Ratio | Color Gamut | Viewing Angle (L/R/U/D) | Key Features |
|-------|----------------------|-----------------|------|------------|---|-----------------|-------------------|----------------|----------------------------|---------------------------------|
| 13.3" | WUXGA (1920x1200) | Multi- touch | IPS | 300 nits | Anti- reflection, Anti- smudge | 16:10 | 1000:1 | 100% sRGB | 85°/85°/85°/85° | - |
| 13.3" | WUXGA (1920x1200) | Multi- touch | IPS | 300 nits | Anti-glare | 16:10 | 1000:1 | 100% sRGB | 85°/85°/85°/85° | - |
| 13.3" | WUXGA (1920x1200) | Multi- touch | IPS | 500 nits | Anti-glare | 16:10 | 1000:1 | 100% sRGB | 85°/85°/85°/85° | ThinkPad® Privacy Guard |
| 13.3" | WQXGA (2560x1600) | Multi- touch | IPS | 400 nits | Anti- reflection, Anti- smudge | 16:10 | 1200:1 | 100% sRGB | 85°/85°/85°/85° | Low power, low blue light |

Touchscreen

OGS (One Glass Solution) multi-touch, supports 10-point touch

Notes:

1. California Electronic Waste Recycling Fee

In California, per state law, Lenovo charges an electronic waste recycling fee on this covered device at the time of sale of the product. For more information, go to https://www.calrecycle.ca.gov/Electronics/Consumer

Multi-mode

Multi-mode

Laptop, tent, stand, and tablet modes supported by 360° hinge

Input Device

Pen

- Lenovo Integrated Pen, with built-in rechargeable battery, 4096 levels of pressure sensitivity, on-board garaged and rechargeable
- No pen (with a pen garage ready, purchase separately)

Keyboard

6-row, spill-resistant, multimedia Fn keys with Unified Communications controls

Keyboard Backlight

LED backlight

UltraNav™

TrackPoint® pointing device and Mylar® surface multi-touch touchpad

Mechanical

Dimensions (WxDxH)[1]

305 x 213.9 x 15.39 mm (12.0 x 8.42 x 0.61 inches)

Weight[2]

Starting at 1.2 kg (2.65 lbs)



Case Color

Black

Case Material

Carbon fiber hybrid (top), carbon fiber hybrid (bottom)

Notes

- 1. The system dimensions may vary depending on configurations.
- 2. The system weight is approximate and based on results in Lenovo lab, which varies depending on the source of component, variance of the distribution of each component, and manufacturing process. It may not be the exact weight for each specific model.

CONNECTIVITY

Network

Ethernet[1]

No onboard Ethernet

WLAN + Bluetooth®[2][3]

Intel Wi-Fi® 6 AX201, 802.11ax 2x2 Wi-Fi + Bluetooth 5.1

WWAN**

- Wireless WAN upgradable to 4G (with antenna ready)
- · Quectel EM120R-GL, 4G LTE CAT12, M.2 card
- Quectel EM120R-GL, 4G LTE CAT12, M.2 card, with embedded eSIM functionality
- No support

SIM Card

- Gemalto eSIM card (physical)
- · No SIM card inbox

NFC

- · Near Field Communication
- No support

Notes:

- 1. Ethernet support via optional Lenovo USB-C to Ethernet Adapter
- 2. Bluetooth 5.2 is hardware ready but may run at a lower version due to OS limitations.
- 3. Wi-Fi 6 full features might be limited by country-level restrictions.

Ports^[1]

Standard Ports

- 1x USB 3.2 Gen 1
- 1x USB 3.2 Gen 1 (Always On)
- 2x Thunderbolt 4 / USB4® 40Gbps (support data transfer, Power Delivery 3.0 and DisplayPort™ 1.4a)
- 1x HDMI 2 C
- 1x Headphone / microphone combo jack (3.5mm)

Optional Ports***

- 1x Smart card reader
- 1x Nano-SIM card slot (WWAN support models)

Notes:

The transfer speed of following ports will vary and, depending on many factors, such as the processing speed of the host device, file
attributes and other factors related to system configuration and your operating environment, will be slower than theoretical speed.
USB 2.0: 480 Mbit/s;

USB 3.2 Gen 1 (SuperSpeed USB 5Gbps, formerly USB 3.0 / USB 3.1 Gen 1): 5 Gbit/s;

USB 3.2 Gen 2 (SuperSpeed USB 10Gbps, formerly USB 3.1 Gen 2): 10 Gbit/s;

USB 3.2 Gen 2x2 (SuperSpeed USB 20Gbps): 20 Gbit/s;

Thunderbolt 3/4: 40 Gbit/s

Docking

Docking

Various docking solutions supported via Thunderbolt / USB-C.

For more compatible docking solutions, please visit Docking for ThinkPad X13 Yoga® Gen 2 (Intel)



Monitor Cable

Monitor Cable***

- Lenovo HDMI to VGA Monitor Adapter
- Lenovo USB-C to VGA Adapter
- Lenovo USB-C to DisplayPort Adapter
- · No monitor cable

SECURITY & PRIVACY

Security

Security Chip

Discrete TPM 2.0, TCG certified

Physical Locks

Kensington® Nano Security Slot™

Smart Card Reader

- · Smart card reader
- No smart card reader

Fingerprint Reader

Touch style fingerprint reader integrated in power button, match-on-chip

BIOS Security

- · Power-on password
- · Supervisor password
- NVMe password
- Self-healing BIOS

Other Security

- Camera privacy shutter
- (Optional) IR camera for Windows Hello
- (Optional) Privacy Guard with Privacy Alert
- (Optional) Human Presence Detection

MANAGEABILITY

System Management

System Management[1]

- Intel vPro®
- Non-vPro

Notes:

1. Intel vPro offers a superset of DASH's defined capabilities.

SERVICE

Warranty

Base Warranty**

- 1-year courier or carry-in service
- 1-year courier or carry-in with 2-year system board service (Korea only)
- 1-year limited onsite service
- 3-year (1-yr battery) courier or carry-in service
- 3-year (1-yr battery) limited onsite service
- · No base warranty

ENVIRONMENTAL

Operating Environment



Temperature[1]

- Operating: 5°C (41°F) to 35°C (95°F)
- Storage and transportation in original shipping package: -20°C (-4°F) to 60°C (140°F)
- Storage without package: 5°C (41°F) to 43°C (109°F)

Humidity

- Operating: 8% to 95% at wet-bulb temperature 23°C (73°F)
- Storage and transportation: 5% to 95% at wet-bulb temperature 27°C (81°F)

Altitude

Maximum altitude (without pressurization): 3048 m (10,000 ft)

Notes:

1. When you charge the battery, its temperature must be no lower than 10°C (50°F).

ACCESSORIES

Bundled Accessories

Bundled Accessories

- · Lenovo USB-C to Ethernet Adapter
- None

CERTIFICATIONS

Green Certifications¹¹

Green Certifications[2]

- EPEAT™ Gold
- ENERGY STAR® 8.0
- TCO Certified
- RoHS compliant

Notes:

- 1. The items listed under the "Green Certifications" section may not only refer to certification but also registration or self-declaration.
- 2. EPEAT is registered where applicable, please see https://www.epeat.net for registration status by country.

Other Certifications

Mil-Spec Test

MIL-STD-810H military test passed

Other Certifications

(Optional) Intel Evo™ Platform

- Feature with ** means that only one offering listed under the feature is configured on selected models.
- Feature with *** means that one or more offerings listed under the feature could be configured on selected models.
- Lenovo reserves the right to change specifications or other product information without notice. Lenovo is not
 responsible for photographic or typographical errors. LENOVO PROVIDES THIS PUBLICATION "AS IS,"
 WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES
 OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some jurisdictions do not allow
 disclaimer of express or implied warranties in certain transactions, therefore this disclaimer may not apply to
 you.
- The specifications on this page may not be available in all regions, and may be changed or updated without







intel

intel



intel.





intel. intel.





intel.