


OVERVIEW



| 1. Thunderbolt 4 | 6. Headphone / microphone combo jack (3.5mm) |
|--|--|
| 2. Thunderbolt 4 | 7. Smart card reader * |
| 3. Ethernet extension connector (mini RJ-45) * | 8. USB 3.2 Gen 1 |
| 4. HDMI 2.0 | 9. Kensington Nano Security Slot |
| 5. USB 3.2 Gen 1 (Always On) | |

Notes:

- Items with * are only available on selected models
- Optional nano-SIM card slot on the rear side (not shown on the sample product above)
- The combination of 2 and 3 is side docking connector



PERFORMANCE

Processor

Processor Family

11th Generation Intel® Core™ i5 / i7 Processor

Processor**

| Processor Name | Cores | Threads | Base Frequency | Max Frequency | Cache | Processor Graphics |
|----------------|-------|---------|----------------|---------------|-------|-------------------------|
| Core i5-1135G7 | 4 | 8 | 2.4GHz | 4.2GHz | 8MB | Intel Iris® Xe Graphics |
| Core i5-1145G7 | 4 | 8 | 2.6GHz | 4.4GHz | 8MB | Intel Iris Xe Graphics |
| Core i7-1165G7 | 4 | 8 | 2.8GHz | 4.7GHz | 12MB | Intel Iris Xe Graphics |
| Core i7-1185G7 | 4 | 8 | 3.0GHz | 4.8GHz | 12MB | Intel Iris Xe Graphics |

Operating System

Operating System**[1]

- Windows® 11 Pro
- Windows 11 Home
- Windows 11 Home Single Language
- Windows 11 DG Windows 10 Pro 64
- Windows 10 Pro 64
- Windows 10 Home 64
- Windows 10 Home 64 Single Language
- Windows 10 IoT Enterprise LTSC
- Linux
- Ubuntu Linux
- · No operating system

Notes:

Graphics

Graphics

| Graphics | Туре | Memory | Key Features | |
|------------------------|------------|--------|---------------|--|
| Intel Iris Xe Graphics | Integrated | Shared | DirectX® 12.1 | |

Monitor Support

Monitor Support [1]

Supports up to 4 independent displays (native display and 3 external monitors via Thunderbolt™ and HDMI®)

- Thunderbolt supports up to 5K@60Hz
- HDMI supports up to 4K@60Hz

Notes:

1. Refresh rates >60hz also supported, however max resolution will be limited.

Chipset

Chipset

Intel SoC (System on Chip) platform

Memory

Max Memory

- 8GB soldered memory, not upgradable
- 16GB soldered memory, not upgradable
- 32GB soldered memory, not upgradable

Memory Slots

Memory soldered to systemboard, no slots, dual-channel

Memory Type

^{1.} Some features may not be supported on the system with Linux preload, including but not limited to Intel RST RAID, MIPI computer vision camera, WWAN, Human Presence Detection, etc.



LPDDR4x-4266

Storage

Storage Support[1]

One drive, up to 256GB M.2 2242 SSD or 2TB M.2 2280 SSD

Storage Type**

| Disk Type | Interface | Security |
|--------------|------------------------------------|----------|
| M.2 2242 SSD | PCIe® NVMe®, PCIe 3.0 x4 | - |
| M.2 2280 SSD | PCIe NVMe, PCIe x4 | Opal 2.0 |
| M.2 2280 SSD | PCIe NVMe, PCIe 4.0 x4 Performance | Opal 2.0 |

Notes:

Removable Storage

Card Reader

No card reader

Multi-Media

Audio Chip

High Definition (HD) Audio, Realtek® ALC3287 codec

Speakers

Stereo speakers, 2W x2, Dolby® Audio™

Microphone

- · Dual-microphone array, far-field
- · No microphone

Camera**

- HD 720p, with privacy shutter, fixed focus
- HD 720p + IR hybrid, with privacy shutter, fixed focus
- FHD 1080p + IR hybrid, with privacy shutter, fixed focus
- No camera

Battery

Battery

Integrated Li-Polymer 57Wh battery, supports Rapid Charge (charge up to 80% in 1hr) with 65W AC adapter

Max Battery Life[1]

MobileMark® 2018: 14.5 hr JEITA 2.0: 23.6 hr

Notes:

1. All battery life claims are approximate maximum and based on results using the MobileMark 2014, MobileMark 2018, JEITA 2.0, continuous 1080p video playback (with 150nits brightness and default volume level) or Google Power Load Test (PLT) battery-life benchmark tests. Actual battery life will vary and depends on many factors such as product configuration and usage, software use, wireless functionality, power management settings, and screen brightness. The maximum capacity of the battery will decrease with time and use.

Power Adapter

Power Adapter**[1][2]

- 45W USB-C $^{\circ}$ (2-pin) AC adapter, supports PD 3.0, 100-240V, 50-60Hz
- 45W USB-C (3-pin) AC adapter, supports PD 3.0, 100-240V, 50-60Hz
- 65W USB-C (2-pin) AC adapter, supports PD 3.0, 100-240V, 50-60Hz
- 65W USB-C (3-pin) AC adapter, supports PD 3.0, 100-240V, 50-60Hz
- 65W USB-C slim (2-pin) AC adapter, supports PD 3.0, 100-240V, 50-60Hz
- 65W USB-C slim (3-pin) AC adapter, supports PD 3.0, 100-240V, 50-60Hz
- No power adapter

^{1.} The storage capacity supported is based on the test results with current Lenovo® storage offerings. The system may support larger storage as the technology develops.



Notes:

- 1. AC adapter offerings depend on the country.
- 2. No power adapter is for special bid only.

DESIGN

Display

Display**[1]

| Size | Resolution | Touch | Туре | Brightness | Surface | Aspect Ratio | Contrast Ratio | Color Gamut | Viewing Angle (L/R/U/D) | Key Features |
|------|--------------------|-----------------|------|------------|----------------|-----------------|-------------------|-----------------------|----------------------------|--------------------------------------|
| 14" | FHD (1920x1080) | None | IPS | 400 nits | Anti- glare | 16:9 | 800:1 | 72% NTSC | 85°/85°/85°/85° | Low power |
| 14" | FHD (1920x1080) | None | IPS | 300 nits | Anti- glare | 16:9 | 700:1 | 45% NTSC | 85°/85°/85°/85° | - |
| 14" | FHD (1920x1080) | Multi- touch | IPS | 300 nits | Anti- glare | 16:9 | 700:1 | 45% NTSC | 85°/85°/85°/85° | - |
| 14" | FHD (1920x1080) | Multi- touch | IPS | 500 nits | Anti- glare | 16:9 | 800:1 | 72% NTSC | 85°/85°/85°/85° | ThinkPad® Privacy Guard |
| 14" | UHD (3840x2160) | None | IPS | 500 nits | Anti- glare | 16:9 | 1500:1 | 100% Adobe® RGB | 85°/85°/85°/85° | Dolby Vision™, DisplayHDR™ 400 |

Touchscreen

- On-cell touch, supports 10-point touch
- Non-touch

Notes:

1. California Electronic Waste Recycling Fee In California USA, per state law, Lenovo charges an electronic waste recycling fee on this covered device at the time of sale of the product. For more information, please go to https://www.calrecycle.ca.gov/Electronics/Consumer

Input Device

Keyboard

6-row, spill-resistant, multimedia Fn keys with Unified Communications controls

Keyboard Backlight

- · LED backlight
- Non-backlight

UltraNav™

TrackPoint® pointing device and Mylar® surface multi-touch touchpad

Mechanical

Dimensions (WxDxH)[1]

| Models | Dimensions | | |
|---|---|--|--|
| Models with black cover and FHD Low Power / UHD display | 327.5 x 224 x 16.14 mm (12.89 x 8.82 x 0.64 inches) | | |
| Models with black cover and FHD touch / FHD non-touch / FHD Privacy Guard display | 327.5 x 224.4 x 16.81 mm (12.89 x 8.83 x 0.66 inches) | | |
| Models with storm grey cover | 327.5 x 225.3 x 16.81 mm (12.89 x 8.87 x 0.66 inches) | | |

Weight^[2]

| Models | Weight |
|---|--------------------------------|
| Models with black cover and FHD Low Power / UHD display | Starting at 1.28 kg (2.83 lbs) |
| Models with black cover and FHD touch / FHD non-touch / FHD Privacy Guard display | Starting at 1.36 kg (2.99 lbs) |
| Models with storm grey cover and FHD Low Power / UHD display | Starting at 1.51 kg (3.32 lbs) |



Models with storm grey cover and FHD touch / FHD non-touch / FHD Privacy Guard display Starting at 1.57 kg (3.46 lbs)

Case Color**

- · Storm grey
- · Villi black

Case Material**

- Villi black models: carbon fiber hybrid (top), magnesium (keyboard cover), aluminium (bottom)
- Storm grey models: aluminium (top), aluminium (keyboard cover & bottom)

Notes:

- 1. The system dimensions may vary depending on configurations.
- 2. The system weight is approximate and based on results in Lenovo lab, which varies depending on the source of component, variance of the distribution of each component, and manufacturing process. It may not be the exact weight for each specific model.

CONNECTIVITY

Network

Ethernet**

- Gigabit Ethernet, Intel Ethernet Connection I219-LM (vPro® models), mini RJ-45 to RJ-45 via optional ThinkPad Ethernet Extension Adapter Gen 2, supports Wake-on-LAN
- Gigabit Ethernet, Intel Ethernet Connection I219-V (non-vPro models), mini RJ-45 to RJ-45 via optional ThinkPad Ethernet Extension Adapter Gen 2, supports Wake-on-LAN
- No onboard Ethernet

WLAN + Bluetooth®**[1][2]

- Intel Wi-Fi® 6 AX200, 802.11ax 2x2 Wi-Fi + Bluetooth 5.1
- Intel Wi-Fi 6 AX201, 802.11ax 2x2 Wi-Fi + Bluetooth 5.1
- Intel Wi-Fi 6E AX210, 802.11ax 2x2 Wi-Fi + Bluetooth 5.1

WWAN**

- Wireless WAN upgradable to 4G (with antenna ready)
- Quectel EM120R-GL, 4G LTE CAT12, M.2 card
- Quectel EM120R-GL, 4G LTE CAT12, M.2 card, with embedded eSIM functionality
- Qualcomm® Snapdragon™ X55 5G Modem-RF System, Sub-6 GHz, M.2 card, with embedded eSIM functionality
- No support

SIM Card

- Gemalto eSIM card (physical)
- No SIM card inbox

NFC

- Near Field Communication
- · No support

Notes:

- 1. Bluetooth 5.2 is hardware ready but may run at a lower version due to OS limitations.
- 2. Wi-Fi 6 and Wi-Fi 6E full features might be limited by country level restrictions.
 6GHz Wi-Fi 6E operation is dependent on the support of the operating system, routers/APs/Gateways that support Wi-Fi 6E, and the regional regulatory certifications & spectrum allocation.

Ports^[1]

Standard Ports

- 1x USB 3.2 Gen 1
- 1x USB 3.2 Gen 1 (Always On)
- 2x Thunderbolt 4 / USB4® 40Gbps (support data transfer, Power Delivery 3.0 and DisplayPort™ 1.4a)
- 1x HDMI 2.0
- 1x Headphone / microphone combo jack (3.5mm)

Optional Ports***[2]

- 1x Ethernet extension connector (mini RJ-45)
- 1x Side docking connector (Ethernet models only)
- 1x Smart card reader
- 1x Nano-SIM card slot (WWAN support models)



Notes:

1. The transfer speed of following ports will vary and, depending on many factors, such as the processing speed of the host device, file attributes and other factors related to system configuration and your operating environment, will be slower than theoretical speed. USB 2.0: 480 Mbit/s;

USB 3.2 Gen 1 (SuperSpeed USB 5Gbps, formerly USB 3.0 / USB 3.1 Gen 1): 5 Gbit/s;

USB 3.2 Gen 2 (SuperSpeed USB 10Gbps, formerly USB 3.1 Gen 2): 10 Gbit/s;

USB4 20Gbps / USB 3.2 Gen 2x2 (SuperSpeed USB 20Gbps): 20 Gbit/s;

USB4 40Gbps (USB 40Gbps): 40 Gbit/s;

Thunderbolt 3/4: 40 Gbit/s

2. Ethernet and side docking connector are coexisting. On some models, both of them are equipped. On some models, neither of them is equipped.

If your computer has Ethernet icon, it supports wired Ethernet connection with ThinkPad Ethernet Extension Adapter or ThinkPad Basic/Pro/Ultra Docking Station.

If your computer does not have Ethernet icon, the Ethernet connector does not support Ethernet connection. We recommend you use the Lenovo USB-C to Ethernet Adapter for Ethernet connection.

Docking

Docking

Various docking solutions supported via side docking connector (optional) or Thunderbolt / USB-C. For more compatible docking solutions, please visit <u>Docking for ThinkPad T14s Gen 2 (Intel)</u>

Monitor Cable

Monitor Cable***

- Lenovo HDMI to VGA Monitor Adapter
- Lenovo USB-C to VGA Adapter
- Lenovo USB-C to DisplayPort Adapter
- · No monitor cable

SECURITY & PRIVACY

Security

Security Chip

Discrete TPM 2.0, TCG certified

Physical Locks

Kensington® Nano Security Slot™

Smart Card Reader

- Smart card reader
- No smart card reader

Fingerprint Reader

- Touch style fingerprint reader integrated in power button, match-on-chip
- · No fingerprint reader

BIOS Security

- Power-on password
- · Supervisor password
- NVMe password
- Self-healing BIOS

Other Security

- (Optional) Camera privacy shutter
- (Optional) IR camera for Windows Hello
- (Optional) Privacy Guard with Privacy Alert
- (Optional) Human Presence Detection

MANAGEABILITY

System Management

System Management[1]

- Intel vPro
- Non-vPro



Notes:

1. Intel vPro offers a superset of DASH's defined capabilities.

SERVICE

Warranty^[1]

Base Warranty**

- 1-year courier or carry-in service
- 1-year courier or carry-in with 2-year system board service (Korea only)
- 1-year limited onsite service
- 3-year (1-yr battery) courier or carry-in service
- 3-year (1-yr battery) limited onsite service
- No base warranty

Notes:

1. The warranty upgrades may be bundled with some models, please check the "Included upgrade" column in the specific model's configurations. For more service extensions, please go to https://smartfind.lenovo.com/. To learn more details of warranty policy, please access https://pcsupport.lenovo.com/warranty.

ENVIRONMENTAL

Operating Environment

Temperature[1]

- Operating: 5°C (41°F) to 35°C (95°F)
- Storage and transportation in original shipping package: -20°C (-4°F) to 60°C (140°F)
- Storage without package: 5°C (41°F) to 43°C (109°F)

Humidity

- Operating: 8% to 95% at wet-bulb temperature 23°C (73°F)
- Storage and transportation: 5% to 95% at wet-bulb temperature 27°C (81°F)

Δltituda

Maximum altitude (without pressurization): 3048 m (10,000 ft)

Notes:

1. When you charge the battery, its temperature must be no lower than 10°C (50°F).

ACCESSORIES

Bundled Accessories

Bundled Accessories***

- · Lenovo USB-C to Ethernet Adapter
- ThinkPad Ethernet Extension Adapter Gen 2
- None

CERTIFICATIONS

Green Certifications¹¹

Green Certifications[2]

- EPEAT™ Gold Registered
- ENERGY STAR® 8.0
- TCO Certified
- RoHS compliant

Notes:

- 1. The items listed under the "Green Certifications" section may not only refer to certification but also registration or self-declaration.
- 2. EPEAT is registered where applicable, please see https://www.epeat.net for registration status by country.

Other Certifications

ThinkPad T14s Gen 2 (Intel)



Mil-Spec Test

MIL-STD-810H military test passed

Other Certifications[1]

(Optional) Intel Evo™ Platform

Notes:

1. Intel Evo is only available for the models with FHD Low Power, FHD Privacy Guard, or UHD display.

- Feature with ** means that only one offering listed under the feature is configured on selected models.
- Feature with *** means that one or more offerings listed under the feature could be configured on selected models.
- Lenovo reserves the right to change specifications or other product information without notice. Lenovo is not
 responsible for photographic or typographical errors. LENOVO PROVIDES THIS PUBLICATION "AS IS,"
 WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES
 OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some jurisdictions do not allow
 disclaimer of express or implied warranties in certain transactions, therefore this disclaimer may not apply to
 you.
- The specifications on this page may not be available in all regions, and may be changed or updated without notice.







intel. intel.





intel

intel.

intel